

General Descriptions

TrendChip's TC3162P2F ADSL2/2+ processor is a highly integrated solution for ADSL broadband access gateway. It employs the advanced technology compliant to the various standards defined by ANSI and ITU-T. It incorporates a DMT engine, a 32-bit high performance network processor, a USB 1.1 client controller & transceiver, a 10/100 Ethernet MAC with MII, an ATM AAL5 hardware SAR and a mini-PCI bridge controller. The 10/100 Ethernet MAC with an external PHY supports LAN access. The 12Mbps USB 1.1 controller with transceiver provides a plug-and-play service for PC without external device. For wireless LAN access, IEEE 802.11a/b/g mini-PCI cards can be used on the mini-PCI card slot. The mini-PCI bridge controller supports up to two client cards. When used with TrendChip's TC3084/TC3085 analog front-end (AFE), it performs a simple two-chip solution for ADSL1/2/2+ bridge/router applications. These features maximize the flexibility for the system designers.

Features

- Support all ADSL standards (ADSL1/2/2+), including Annex A, B, I, J & M.
- Support Reach-Extended ADSL2 (Annex L).
- Two-chip ADSL bridge/router solution including TC3162P2F ADSL2/2+ processor and TC3084/TC3085 integrated analog front end and line driver
- Compliant to ADSL performance requirements of DSL Forum and operator's specifications (including INP requirement)
- 32-bit high performance network processor core with MMU and cache
- Integrated 10/100 Ethernet MAC with MII for LAN access
- Embedded hardware ATM AAL-5 SAR supports CBR, UBR and VBR, and GFR traffics
- USB 1.1 controller provides plug-and-play service for personal computers.
- Mini-PCI bridge controller supports up to two client cards.
- JTAG supported with ICE debug capability
- 1.8V/3.3V supply
- 208-pin PQFP package

